


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G06F 1/16	A1	(11) International Publication Number: WO 95/23368 (43) International Publication Date: 31 August 1995 (31.08.95)
(21) International Application Number: PCT/US95/01938 (22) International Filing Date: 23 February 1995 (23.02.95) (30) Priority Data: 200,078 23 February 1994 (23.02.94) US (71) Applicant (for all designated States except US): MINISTOR PERIPHERALS INTERNATIONAL LIMITED [US/US]; 2801 Orchard Parkway, San Jose, CA 95134 (US). (72) Inventors; and (75) Inventors/Applicants (for US only): HAZEBROUCK, Henry, B. [US/US]; 1145 W. McKinley Avenue, Sunnyvale, CA 94086 (US). GRIFFIN, Gary, C. [US/US]; 254 Hilton Drive, Boulder Creek, CA 95006 (US). URIU, David, H. [US/US]; 1925 Cronwell Drive, San Jose, CA 95125 (US). (74) Agent: RITCHIE, David, B.; D'Alessandro & Ritchie, P.O. Box 640640, San Jose, CA 95164-0640 (US).		(81) Designated States: AU, CA, JP, KR, SG, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report.

(54) Title: FLEXIBLE PULL TAB FOR PCMCIA ELECTRONICS PACKAGES

(57) Abstract

A miniature disk drive (12) or other electronics package, for example a modem, which is designed to be removably connected to a PCMCIA type I, II, III, or IV interface receptacle of a computer or expansion chassis is provided with a PCMCIA-type interface connector (20) for connection to the PCMCIA interface and a pull tab (26) on the electronics package directly opposite the connector. The pull tab is flexible and tear resistant and is mounted to the PCMCIA electronics package so that when the tab is pulled, the PCMCIA electronics package may be pulled from the PCMCIA receptacle regardless of how much of the PCMCIA electronics package protrudes from the computer or expansion chassis. Accordingly, the PCMCIA electronics package may be made smaller in length than would otherwise be necessary in order for a user to retrieve it from the PCMCIA slot.



Best Available Copy

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

TITLE OF THE INVENTION

FLEXIBLE PULL TAB FOR PCMCIA ELECTRONICS PACKAGES

BACKGROUND OF THE INVENTION1. Field of the Invention

This invention relates to the field of miniature electronics packages which interface to other electronic devices by means of a PCMCIA-type interface. More particularly, this invention is related to PCMCIA-type electronics packages such as hard disk drives and modems which interface to computers via PCMCIA type I (single height), type II (double height), type III (triple height), and type IV (quadruple height), etc. interface connectors.

2. The Prior Art

Miniature hard disk drives which interface to a computer via a PCMCIA-type interface were introduced by MiniStor Peripherals Corporation of San Jose, California at a press conference in San Jose, California in March of 1992. Hard disk drives of this type are described more fully in co-pending U.S. Patent Application serial no. 08/035,458 filed March 23, 1993 which is hereby incorporated herein by reference as if set forth fully herein. PCMCIA-type drives provide a convenient pocket-

sized mass storage medium which can be easily carried from computer to computer by a user. Other PCMCIA-type devices include modems, RAM modules, flash memory modules, ethernet adapters and the like and are presently available from a wide variety of vendors.

The PCMCIA interface connector is a 68 pin connector which requires force to engage and disengage. While engaging the interface connectors is quite straightforward and can be accomplished by simply pushing the PCMCIA-type electronics package into the mating receptacle on the computer or expansion chassis, removal can be a little more complicated where the PCMCIA electronics package does not protrude much from the computer or expansion chassis slot where it attaches to the computer. In some cases pliers and other tools are required in order to remove the PCMCIA electronics package from its slot.

OBJECTS AND ADVANTAGES OF THE INVENTION

Accordingly, it is an object of the present invention to provide an improved PCMCIA electronics package structure which facilitates removal of the PCMCIA electronics package from the PCMCIA slot.

These and many other objects and advantages of the present invention will become apparent to those of ordinary skill in the art from a consideration of the drawings and ensuing description of the invention.

SUMMARY OF THE INVENTION

A miniature disk drive or other miniature electronics package such as, for example, a modem, which is designed to be removably connected to a PCMCIA type I, type II, type III, or type IV interface receptacle of a computer or expansion chassis is provided with a PCMCIA-type interface connector for connection to the PCMCIA interface and a pull tab on the side of the electronics package directly opposite the side of the electronics package on which is mounted the PCMCIA-type interface connector. The pull tab is flexible and tear resistant and is mounted to the PCMCIA electronics package so that when the tab is pulled, the PCMCIA electronics package may be pulled from the PCMCIA receptacle regardless of how much of the PCMCIA electronics package protrudes from the computer or expansion chassis. Accordingly, the computer or expansion chassis may fully enclose the PCMCIA electronics package while the package remains easily removable with the pull tab. Also, the PCMCIA electronics package may be made smaller in length than would otherwise be necessary in order for a user to retrieve it from the PCMCIA slot.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a front top perspective exploded view of a PCMCIA electronics package according to a preferred embodiment of the present invention.

FIGS. 2A-2F show the construction and assembly of a pull tab according to a presently preferred embodiment of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Those of ordinary skill in the art will realize that the following description of the present invention is illustrative only and is not intended to be in any way limiting. Other embodiments of the invention will readily suggest themselves to such skilled persons from an examination of the within disclosure.

According to a preferred embodiment of the present invention, a pull tab is provided on an electronics package or "card" designed to meet the well known PCMCIA specifications. According to these specifications which are well known to those of skill in the art, A PCMCIA interfaceable electronics package occupies a volume having a width of about 5.4 cm (the specification calls for a width of 54 mm \pm 0.1 mm), a length of about 8.6 cm (86 mm) or less, and a height of 0.33 cm (3.3 mm) in the case of a PCMCIA Type-I card, a height of 0.50 cm (5.0 mm) in the case of a PCMCIA Type-II card, a height of 1.05 cm (10.5 mm) in the case of a PCMCIA Type-III card, a height of 1.25 cm (12.5 mm) or greater in the case of a PCMCIA Type-IV card. Technically the PCMCIA Type-IV has yet to be approved by the standards committee for PCMCIA cards, however, as used herein a Type-IV

card refers to cards thicker (of greater height) than a Type-III card. A 68-socket female PCMCIA connector is disposed at one end of the card and positioned so as to mate with a mating male 68-pin PCMCIA connector in a corresponding PCMCIA Type-I, Type-II, Type-III, or Type-IV slot in a computer or expansion chassis (collectively referred to herein as a "computing device"). In the common configuration used in notebook computers manufactured, for example, by I.B.M. of Armonk, New York and Toshiba of Japan, the PCMCIA interface consists of a recessed slot in the notebook computer with the male PCMCIA connector located all the way inside the slot. In use, the PCMCIA cards are inserted into the slot and pushed into engagement with the PCMCIA connector in the slot.

Because it is generally considered to be undesirable to have objects protruding very far from the notebook computer, most PCMCIA slots are designed to contain most or all of the body of the PCMCIA card. This feature can make retrieval of the PCMCIA card from the slot difficult at times, particularly where the PCMCIA card has a relatively short length.

In accordance with the present invention, a pull tab is provided which is securely fixed to a PCMCIA electronics package and which can be used as an aid in retrieving a PCMCIA card from its slot in a computing device.

Turning now to the drawings, FIG. 1 is an exploded perspective drawing of a PCMCIA disk drive card 10 according to a

first preferred embodiment of the present invention. Drive card 10 comprises the disk drive mechanical package 12, an insulation sheet 14, a cover plate 16, the disk drive electronics contained on a printed circuit board 18 which includes female 68-socket PCMCIA connector 20. A bottom cover plate 22 is also included which is attached to the rest of the package by screws 24 which hold the entire assembly together as shown. Pull tab 26 is also included and extends from the card on the side directly opposite the PCMCIA connector 20. According to a first preferred embodiment, pull tab 26 is adhered to the upper portion 28 of bottom cover plate 22 and comprises an attachment portion 30 and a loop portion 32. The attachment portion 30 is, in the final assembly of the card 10 contained within the card and adhered to bottom cover plate 22 and the loop portion 32 extends outside card 10 and may be used as a retrieval aid for getting the card out of a corresponding PCMCIA slot.

Turning now to FIGS. 2A-2F the details of the pull tab according to a first preferred embodiment of the invention are shown. In FIG. 2A the basic pull tab preform 34 is shown. Pull tab preform 34 comprises a lower portion 36, a top portion 38, and a rubber adhesive portion 40. Lower portion 36 is preferably fabricated from a polyester tape such as 3M type 8422 tape approximately 0.0014 in (0.0036 cm) thick. To the top of lower portion 36 is adhered rubber adhesive portion 40. 3M type 8422 tape includes the polyester film and the rubber adhesive. Other

equivalent materials could also be used as would be known to those of skill in the art. The total thickness of lower portion 36 and rubber adhesive portion 40 is about 0.0025 in (0.0064 cm).

Referring now to FIG. 2B, top portion 38 comprises three horizontal sections. First top section 42, second top section 44 and third top section 46. First top section 42 is preferably a paper release material which can be removed to expose adhesive layer 40 below first top section 42. Third top section 46 is similarly preferably a paper release material which can be removed to expose adhesive layer 40 below third top section 46. Second top section 44 is preferably a fabric material, resistant to tearing, such as Industrial Coatings Group, Inc. Type Arrestox B, which is fully adhered to adhesive layer 40. Similar materials could also be used as would be known to those of skill in the art.

Assembly of the pull tab proceeds as shown in FIGS. 2C-2F. First top section 42 is removed and lower portion 36 is doubled over and adhered to itself as shown in FIG. 2C to form the subassembly shown in FIG. 2D. Next, the subassembly is folded in half as shown in FIG. 2E to form the subassembly shown in FIG 2F. Finally, the third top section 46 is removed to expose the rubber adhesive layer 40 and the pull tab assembly is then adhered to the upper portion 28 of bottom cover plate 22 as shown in FIG. 1.

Those of skill in the art will readily see that other

pull tab configurations could be used, such as a full fabric pull tab, attachment by hardware instead of or in addition to adhesive, and the like.

While illustrative embodiments and applications of this invention have been shown and described, it would be apparent to those skilled in the art that many more modifications than have been mentioned above are possible without departing from the inventive concepts set forth herein. The invention, therefore, is not to be limited except in the spirit of the appended claims.

CLAIMS

What is claimed is:

1. A PCMCIA electronics package comprising:
a body containing an electrical device interfaceable to a computing device through a PCMCIA interface;
a female PCMCIA connector disposed at one end of said body;
a flexible pull tab extending from an end directly opposite said one end of said body.
2. The PCMCIA electronics package of claim 1 wherein said flexible pull tab is adhesively anchored to an interior wall of said body.
3. The PCMCIA electronics package of claim 1 further comprising a hard disk drive apparatus contained within said body.
4. The PCMCIA electronics package of claim 2 further comprising a hard disk drive apparatus contained within said body.










FIG. 1



INTERNATIONAL SEARCH REPORT

International application No.
PCT/US95/01938

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) : G06F 1/16

US CL : 361/685; 16/110R; 439/483

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 361/683-686, 725-731, 754, 798; 16/110R; 439/483, 484, 476, 928; 360/137; 312/223.2; 364/708.1

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US, A, 5,155,662 (I-SHOU) 13 October 1992, see the entire document.	1-4
Y	US, A, 4,310,208 (WEBSTER ET AL) 12 January 1982, abstract and column 8, lines 19-21.	1-4

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A" document defining the general state of the art which is not considered to be of particular relevance	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"E" earlier document published on or after the international filing date	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"A" document member of the same patent family
"O" document referring to an oral disclosure, use, exhibition or other means	
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

10 APRIL 1995

Date of mailing of the international search report

20 APR 1995

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

MICHAEL W. PHILLIPS

Telephone No. (703) 308-3191

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)